


## QIAOXIN N-Channel Super Trench Power MOSFET

### Description

The VCRRP0178AK uses **Super Trench** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of  $R_{DS(ON)}$  and  $Q_g$ . This device is ideal for high-frequency switching and synchronous rectification.




Schematic diagram

### General Features

- $V_{DS} = 100V, I_D = 78A$
- $R_{DS(ON)} = 7.2m\Omega$ (typical) @  $V_{GS}=10V$
- $R_{DS(ON)} = 9.5m\Omega$ (typical) @  $V_{GS}=4.5V$
- Excellent gate charge  $\times R_{DS(on)}$  product(FOM)
- Very low on-resistance  $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating
- 100% UIS tested

### Application

- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification



TO-252-2L top view

### Package Marking and Ordering Information

| Device Marking | Device | Device Package |
|----------------|--------|----------------|
| VCRRP0178AK    |        | TO-252-2L      |

### Absolute Maximum Ratings ( $T_C=25^\circ C$ unless otherwise noted)

| Parameter   | Symbol              | Limit      | Unit |
|---|---------------------|------------|------|
| Drain-Source Voltage                              | $V_{DS}$            | 100        | V    |
| Gate-Source Voltage                               | $V_{GS}$            | $\pm 20$   | V    |
| Drain Current-Continuous                          | $I_D$               | 78         | A    |
| Drain Current-Continuous( $T_C=100^\circ C$ )     | $I_D (100^\circ C)$ | 60         | A    |
| Pulsed Drain Current                              | $I_{DM}$            | 320        | A    |
| Maximum Power Dissipation                         | $P_D$               | 125        | W    |
| Derating factor                                   |                     | 0.83       | W/°C |
| Single pulse avalanche energy <sup>(Note 5)</sup> | $E_{AS}$            | 320        | mJ   |
| Operating Junction and Storage Temperature Range  | $T_J, T_{STG}$      | -55 To 175 | °C   |

## Thermal Characteristic

|  |                  |     |      |
|--|------------------|-----|------|
| Thermal Resistance, Junction-to-Case <sup>(Note 2)</sup> | R <sub>θJC</sub> | 1.2 | °C/W |
|--|------------------|-----|------|

## Electrical Characteristics (T<sub>C</sub>=25°C unless otherwise noted)


| Parameter  | Symbol              | Condition   | Min | Typ  | Max  | Unit |
|--|---------------------|---|-----|------|------|------|
| <b>Off Characteristics</b>                           |                     |   |     |      |      |      |
| Drain-Source Breakdown Voltage                       | BV <sub>DSS</sub>   | V <sub>GS</sub> =0V I <sub>D</sub> =250μA   | 100 |      | -    | V    |
| Zero Gate Voltage Drain Current                      | I <sub>DSS</sub>    | V <sub>DS</sub> =100V, V <sub>GS</sub> =0V  | -   | -    | 1    | μA   |
| Gate-Body Leakage Current                            | I <sub>GSS</sub>    | V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V  | -   | -    | ±100 | nA   |
| <b>On Characteristics</b> <sup>(Note 3)</sup>        |                     |   |     |      |      |      |
| Gate Threshold Voltage                               | V <sub>GS(th)</sub> | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                                      | 1.2 | 1.7  | 2.2  | V    |
| Drain-Source On-State Resistance                     | R <sub>Ds(ON)</sub> | V <sub>GS</sub> =10V, I <sub>D</sub> =39A   | -   | 7.2  | 8.5  | mΩ   |
|  |                     | V <sub>GS</sub> =4.5V, I <sub>D</sub> =39A  | -   | 9.5  | 12   | mΩ   |
| Forward Transconductance                             | g <sub>FS</sub>     | V <sub>DS</sub> =10V, I <sub>D</sub> =39A   | 40  | -    | -    | S    |
| <b>Dynamic Characteristics</b> <sup>(Note 4)</sup>   |                     |   |     |      |      |      |
| Input Capacitance                                    | C <sub>iss</sub>    | V <sub>DS</sub> =50V, V <sub>GS</sub> =0V,<br>F=1.0MHz  | -   | 4200 | 5480 | PF   |
| Output Capacitance                                   | C <sub>oss</sub>    |   | -   | 354  | 425  | PF   |
| Reverse Transfer Capacitance                         | C <sub>rss</sub>    |   | -   | 23   | 30   | PF   |
| <b>Switching Characteristics</b> <sup>(Note 4)</sup> |                     |   |     |      |      |      |
| Turn-on Delay Time                                   | t <sub>d(on)</sub>  | V <sub>DD</sub> =50V, I <sub>D</sub> =39A<br>V <sub>GS</sub> =10V, R <sub>G</sub> =4.7Ω       | -   | 15   | -    | nS   |
| Turn-on Rise Time                                    | t <sub>r</sub>      |   | -   | 10   | -    | nS   |
| Turn-Off Delay Time                                  | t <sub>d(off)</sub> |   | -   | 41   | -    | nS   |
| Turn-Off Fall Time                                   | t <sub>f</sub>      |   | -   | 6    | -    | nS   |
| Total Gate Charge                                    | Q <sub>g</sub>      | V <sub>DS</sub> =50V, I <sub>D</sub> =39A,<br>V <sub>GS</sub> =10V                            | -   | 65   |      | nC   |
| Gate-Source Charge                                   | Q <sub>gs</sub>     |   | -   | 15.3 |      | nC   |
| Gate-Drain Charge                                    | Q <sub>gd</sub>     |   | -   | 9    |      | nC   |
| <b>Drain-Source Diode Characteristics</b>            |                     |   |     |      |      |      |
| Diode Forward Voltage <sup>(Note 3)</sup>            | V <sub>SD</sub>     | V <sub>GS</sub> =0V, I <sub>S</sub> =78A  | -   |      | 1.2  | V    |
| Diode Forward Current <sup>(Note 2)</sup>            | I <sub>S</sub>      |   | -   | -    | 78   | A    |
| Reverse Recovery Time                                | t <sub>rr</sub>     | T <sub>J</sub> = 25°C, I <sub>F</sub> = I <sub>S</sub><br>di/dt = 100A/μs <sup>(Note 3)</sup> | -   | 101  |      | nS   |
| Reverse Recovery Charge                              | Q <sub>rr</sub>     |   | -   | 193  |      | nC   |

## Notes:


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production
5. EAS condition : T<sub>j</sub>=25°C, V<sub>DD</sub>=50V, V<sub>G</sub>=10V, L=0.5mH, R<sub>g</sub>=25Ω

## Test Circuit


### 1) E<sub>AS</sub> test Circuit



### 2) Gate charge test Circuit



### 3) Switch Time Test Circuit



### Typical Electrical and Thermal Characteristics




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 Rdson- Drain Current




Figure 4 Rdson-JunctionTemperature




Figure 5 Gate Charge







Figure 6 Source- Drain Diode Forward




**Figure 7 Capacitance vs Vds**




**Figure 9  $BV_{DSS}$  vs Junction Temperature**



**Figure 8 Safe Operation Area**




**Figure 10 Current De-rating**



**Figure 11 Normalized Maximum Transient Thermal Impedance**

## TO-252 Package Information



| Symbol | Dimensions In Millimeters |        | Dimensions In Inches |       |
|--------|---------------------------|--------|----------------------|-------|
|        | Min.                      | Max.   | Min.                 | Max.  |
| A      | 2.200                     | 2.400  | 0.087                | 0.094 |
| A1     | 0.000                     | 0.127  | 0.000                | 0.005 |
| b      | 0.660                     | 0.860  | 0.026                | 0.034 |
| c      | 0.460                     | 0.580  | 0.018                | 0.023 |
| D      | 6.500                     | 6.700  | 0.256                | 0.264 |
| D1     | 5.100                     | 5.460  | 0.201                | 0.215 |
| D2     | 4.83 TYP.                 |        | 0.190 TYP.           |       |
| E      | 6.000                     | 6.200  | 0.236                | 0.244 |
| e      | 2.186                     | 2.386  | 0.086                | 0.094 |
| L      | 9.800                     | 10.400 | 0.386                | 0.409 |
| L1     | 2.900 TYP.                |        | 0.114 TYP.           |       |
| L2     | 1.400                     | 1.700  | 0.055                | 0.067 |
| L3     | 1.600 TYP.                |        | 0.063 TYP.           |       |
| L4     | 0.600                     | 1.000  | 0.024                | 0.039 |
| Φ      | 1.100                     | 1.300  | 0.043                | 0.051 |
| θ      | 0°                        | 8°     | 0°                   | 8°    |
| h      | 0.000                     | 0.300  | 0.000                | 0.012 |
| V      | 5.350 TYP.                |        | 0.211 TYP.           |       |

### Attention

QIAOXIN assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all QIAOXIN products described or contained herein. QIAOXIN products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. QIAOXIN reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.