

## QIAOXIN N-Channel Super Trench II Power MOSFET

### Description

The series of devices uses **Super Trench II** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of  $R_{DS(on)}$  and  $Q_g$ . This device is ideal for high-frequency switching and synchronous rectification.

### Application

- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification



### General Features

- $V_{DS} = 100V, I_D = 240A$
- $R_{DS(on)} = 2.1m\Omega$ , typical (TO-220)@  $V_{GS} = 10V$
- $R_{DS(on)} = 1.9m\Omega$ , typical (TO-263)@  $V_{GS} = 10V$
- Excellent gate charge x  $R_{DS(on)}$  product(FOM)
- Very low on-resistance  $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating

TO-220



TO-263



Schematic Diagram

### Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VCRRP023N10	VCRRP023N10	TO-220	-	-	-
VCRRP023N10D	VCRRP023N10D	TO-263	-	-	-

### Absolute Maximum Ratings ( $T_c=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	100	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current-Continuous	$I_D$	240	A
Drain Current-Continuous( $T_c=100^\circ C$ )	$I_D(100^\circ C)$	170	A
Pulsed Drain Current	$I_{DM}$	960	A
Maximum Power Dissipation	$P_D$	340	W
Derating factor		2.27	W/ $^\circ C$
Single pulse avalanche energy (Note 4)	$E_{AS}$	2332	mJ
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 To 175	$^\circ C$

## Thermal Characteristic

Thermal Resistance,Junction-to-Case	$R_{\theta JC}$	0.44	°C/W
Thermal Resistance,Junction-to-Ambient (Note 2)	$R_{\theta JA}$	60	°C/W


## Electrical Characteristics ( $T_c=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit	
<b>Off Characteristics</b>							
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	100		-	V	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100V, V_{GS}=0V$	-	-	1	μA	
Gate-Body Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	$\pm 100$	nA	
<b>On Characteristics</b> (Note 2)							
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0	3.0	4.0	V	
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=120A$	TO-220	-	2.1	2.3	mΩ
			TO-263		1.9	2.3	mΩ
Gate resistance	$R_G$		-	2.9	-	Ω	
Forward Transconductance	$g_{FS}$	$V_{DS}=5V, I_D=120A$		200	-	S	
<b>Dynamic Characteristics</b> (Note 3)							
Input Capacitance	$C_{iss}$	$V_{DS}=50V, V_{GS}=0V, F=1.0MHz$	-	17000	-	PF	
Output Capacitance	$C_{oss}$		-	1500	-	PF	
Reverse Transfer Capacitance	$C_{rss}$		-	77	-	PF	
<b>Switching Characteristics</b> (Note 3)							
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=50V, I_D=120A$ $V_{GS}=10V, R_G=1.6\Omega$	-	37	-	nS	
Turn-on Rise Time	$t_r$		-	29	-	nS	
Turn-Off Delay Time	$t_{d(off)}$		-	82	-	nS	
Turn-Off Fall Time	$t_f$		-	34	-	nS	
Total Gate Charge	$Q_g$	$V_{DS}=50V, I_D=120A, V_{GS}=10V$	-	252	-	nC	
Gate-Source Charge	$Q_{gs}$		-	72	-	nC	
Gate-Drain Charge	$Q_{gd}$		-	63	-	nC	
<b>Drain-Source Diode Characteristics</b>							
Diode Forward Voltage (Note 3)	$V_{SD}$	$V_{GS}=0V, I_S=120A$	-		1.2	V	
Diode Forward Current (Note 2)	$I_S$		-	-	240	A	
Reverse Recovery Time	$t_{rr}$	$T_J = 25^\circ C, I_F = 120A$	-	105	-	nS	
Reverse Recovery Charge	$Q_{rr}$	$di/dt = 100A/\mu s$ (Note 2)	-	290	-	nC	


### Notes:

- Repetitive Rating: Pulse width limited by maximum junction temperature.
- The value of  $R_{\theta JA}$  is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with  $T_A = 25^\circ C$ . The Power dissipation  $P_{DSM}$  is based on  $R_{\theta JA}$  and the maximum allowed junction temperature of  $150^\circ C$ . The value in any given application depends on the user's specific board design, and the maximum temperature of  $175^\circ C$  may be used if the PCB allows it.
- Guaranteed by design, not subject to production
- EAS condition :  $T_j=25^\circ C, V_{DD}=50V, V_G=10V, L=0.5mH, R_g=25\Omega$


## Typical Electrical and Thermal Characteristics




**Figure 1 Output Characteristics**




**Figure 4  $R_{DSON}$ -Junction Temperature**




**Figure 2 Transfer Characteristics**




**Figure 5 Gate Charge**




**Figure 3  $R_{DSON}$ - Drain Current**




**Figure 6 Source- Drain Diode Forward**




**Figure 7 Capacitance vs Vds**




**Figure 9 Power De-rating**



**Figure 8 Safe Operation Area**




**Figure 10 Current De-rating**




**Figure 11 Normalized Maximum Transient Thermal Impedance**

## TO-220-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.400	4.600	0.173	0.181
A1	2.250	2.550	0.089	0.100
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.330	0.650	0.013	0.026
c1	1.200	1.400	0.047	0.055
D	9.910	10.250	0.390	0.404
E	8.9500	9.750	0.352	0.384
E1	12.650	12.950	0.498	0.510
e	2.540 TYP.		0.100 TYP.	
e1	4.980	5.180	0.196	0.204
F	2.650	2.950	0.104	0.116
H	7.900	8.100	0.311	0.319
h	0.000	0.300	0.000	0.012
L	12.900	13.400	0.508	0.528
L1	2.850	3.250	0.112	0.128
V	6.900 REF.		0.276 REF.	
Φ	3.400	3.800	0.134	0.150

## TO-263-2L Package Information



SYMBOL	DIMENSIONS		
	MIN.	NOM.	MAX.
A	4.24	4.44	4.64
A1	0.00	0.10	0.25
b	0.70	0.80	0.90
b1	1.20	1.55	1.75
b2	1.20	1.45	1.70
c	0.40	0.50	0.60
c2	1.15	1.27	1.40
D	8.82	8.92	9.02
D1	6.86	7.65	—
E	9.96	10.16	10.36
E1	6.89	7.77	7.89
e	2.54 BSC		
H	14.61	15.00	15.88
L	1.78	2.32	2.79
L1	1.36 REF.		
L2	1.50 REF.		
L3	0.25 BSC		
Q	2.30	2.48	2.70

### **Attention**

QIAOXIN assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all QIAOXIN products described or contained herein. QIAOXIN products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. QIAOXIN reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.