

VCRR P-Channel Enhancement Mode Power MOSFET

Description


The VCRR60P70D uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

General Features


- $V_{DS} = -60V, I_D = -70A$
- $R_{DS(ON)} < 18m\Omega @ V_{GS} = -10V$
- High density cell design for ultra low $R_{DS(on)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation

Application

- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply



Schematic diagram



Marking and pin assignment



TO-263-2L top view

Package Marking and Ordering Information

Device Marking	Device	Device Package
VCRR60P70D		TO-263-2L

Absolute Maximum Ratings ($T_C=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	-70	A
Drain Current-Continuous($T_C=100^\circ C$)	$I_D (100^\circ C)$	-49.5	A
Pulsed Drain Current	I_{DM}	280	A
Maximum Power Dissipation	P_D	200	W
Derating factor		1.33	W/ $^\circ C$
Single pulse avalanche energy ^(Note 5)	E_{AS}	TBD	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 175	$^\circ C$

Thermal Characteristic

Thermal Resistance, Junction-to-Case ^(Note 2)	$R_{\theta JC}$	0.75	$^\circ C/W$
--	-----------------	------	--------------

Electrical Characteristics ($T_C=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=-250\mu\text{A}$	-60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}}=-60\text{V}, V_{\text{GS}}=0\text{V}$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{\text{GS}}=\pm20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	±100	nA
On Characteristics ^(Note 3)						
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=-250\mu\text{A}$	-1.0	-1.75	-2.5	V
Drain-Source On-State Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=-10\text{V}, I_{\text{D}}=-20\text{A}$	-	15.5	18	$\text{m}\Omega$
Forward Transconductance	g_{FS}	$V_{\text{DS}}=-5\text{V}, I_{\text{D}}=-20\text{A}$	-	TBD	-	S
Dynamic Characteristics ^(Note4)						
Input Capacitance	C_{iss}	$V_{\text{DS}}=-30\text{V}, V_{\text{GS}}=0\text{V}, F=1.0\text{MHz}$	-	3850	-	PF
Output Capacitance	C_{oss}		-	249	-	PF
Reverse Transfer Capacitance	C_{rss}		-	194	-	PF
Switching Characteristics ^(Note 4)						
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}}=-30\text{V}, I_{\text{D}}=-20\text{A}$ $V_{\text{GS}}=-10\text{V}, R_{\text{GEN}}=3\Omega$	-	TBD	-	nS
Turn-on Rise Time	t_r		-	TBD	-	nS
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$		-	TBD	-	nS
Turn-Off Fall Time	t_f		-	TBD	-	nS
Total Gate Charge	Q_g	$V_{\text{DS}}=-30\text{V}, I_{\text{D}}=-20\text{A}, V_{\text{GS}}=-10\text{V}$	-	73	-	nC
Gate-Source Charge	Q_{gs}		-	14	-	nC
Gate-Drain Charge	Q_{gd}		-	18	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage ^(Note 3)	V_{SD}	$V_{\text{GS}}=0\text{V}, I_{\text{S}}=-20\text{A}$	-	-	1.2	V
Diode Forward Current ^(Note 2)	I_{S}		-	-	-70	A
Reverse Recovery Time	t_{rr}	$T_J = 25^\circ\text{C}, IF = -20\text{A}$ $di/dt = 100\text{A}/\mu\text{s}$ ^(Note3)	-	TBD	-	nS
Reverse Recovery Charge	Q_{rr}		-	TBD	-	nC

Notes:


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production
5. E_{AS} condition: $T_j=25^\circ\text{C}, V_{\text{DD}}=-30\text{V}, V_{\text{G}}=-10\text{V}, L=0.5\text{mH}, R_g=25\Omega$

Test Circuit


1) E_{AS} Test Circuit




2) Gate Charge Test Circuit



3) Switch Time Test Circuit



TO-263-2L Package Information



COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	4.40	4.57	4.70
A1	0	0.10	0.25
A2	2.59	2.69	2.79
b	0.77	-	0.90
b1	0.76	0.81	0.86
b2	1.23	-	1.36
b3	1.22	1.27	1.32
c	0.34	-	0.47
c1	0.33	0.38	0.43
c2	1.22	-	1.32
D	9.05	9.15	9.25
D1	6.60	-	-
E	10.06	10.16	10.26
E1	7.80	-	8.20
e	2.54BSC		
H	14.70	15.10	15.50
L	2.00	2.30	2.60
L1	1.17	1.27	1.40
L2	-	-	1.75
L3	0.25BSC		
L4	2.00REF		
θ	0°	-	8°
θ_1	5°	7°	9°
θ_2	1°	3°	5°

Attention

QIAOXIN assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all QIAOXIN products described or contained herein. QIAOXIN products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. QIAOXIN reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.